

flannelsuede

Specifications

Contents:

Quality 3100
Quality 3103

38% Recycled Polyester, 35% Polyester, 15% Nylon, 12% Polyurethane
46% Recycled Polyester, 42% Polyester, 12% Polyurethane

Width:

56"

Weight:

13.3 oz. per Linear Yard / 274 Grams per Square Meter

Thickness:

0.84mm

Durability:

Wyzenbeek:
Martindale:

75,000 Double Rubs
Heavy Duty Contract

Fabric Strength:

ASTM D-5034

Exceeds Industry Standards

Piling Resistance:

ASTM D-3511

Exceeds Industry Standards

Seam Strength:

ASTM D-4034

Exceeds Industry Standards

Colorfastness:

Color Rub-Off (AATCC-8 Crocking)
To Light (AATCC-16E)

Exceeds Industry Standards
Exceeds Industry Standards

Fire Test Compliance:

UFAC Cig. Smoldering Test
NFPA-260
CA TB-117 Sec. E
ASTM E-84 Tunnel Test
(Adhered & Unadhered)

Complies with Industry Standards
Complies with Industry Standards
Complies with Industry Standards
Complies with Industry Standards

Maintenance & Care

Water or solvent based cleaning agent
machine washable or dry-cleanable

Flannelsuede contains high-purity recycled polyester from post-consumer and post-industrial sources.

The advanced recycling process uses significantly less energy, eliminates the use of toxic organic solvents, and emits less carbon dioxide than the manufacture of virgin polyester.

Flannelsuede is manufactured in an ISO 14001 / ISO 9001:2000 certified facility and complies with Oeko-Tex Standard 100.