

sensuede

Specifications

Contents:	88% Recycled Polyester, 12% Polyurethane
Width:	56"
Weight:	13.2 oz. per Linear Yard / 275 Grams per Square Meter
Thickness:	0.84mm
Durability: Wyzenbeek: Martindale:	100,000 Double Rubs Heavy Duty Contract
Fabric Strength: ASTM D-5034	Exceeds Industry Standards
Piling Resistance: ASTM D-3511	Exceeds Industry Standards
Seam Strength: ASTM D-4034	Exceeds Industry Standards
Colorfastness: Color Rub-Off (AATCC-8 Crocking) To Light (AATCC-16E)	Exceeds Industry Standards Exceeds Industry Standards
Fire Test Compliance: UFAC Cig. Smoldering Test NFPA-260 CA TB-117 Sec. E ASTM E-84 Tunnel Test (Adhered & Unadhered)	Complies with Industry Standards Complies with Industry Standards Complies with Industry Standards Complies with Industry Standards
Maintenance & Care	Water or solvent based cleaning agent machine washable or dry-cleanable

Sensuede contains high-purity recycled polyester from post-consumer and post-industrial sources.

The advanced recycling process uses significantly less energy, eliminates the use of toxic organic solvents, and emits less carbon dioxide than the manufacture of virgin polyester.

Sensuede is manufactured in an ISO 14001 / ISO 9001:2000 certified facility and complies with Oeko-Tex Standard 100.